



ROBCO 380



ROBCO 380 is a superior quality packing made from long line flax yarn, lubricated by a process which retards extraction. Stock type is made with a tallow compound.

Possible Applications

ROBCO 380 is an ideal packing in cool to moderate temperatures for liquids whose conditions fall close to neutrality on the pH scale. It can be used under moderate temperatures and pressures, cold or lukewarm water, sea water, reciprocating or rotary equipment, piston rods, agitator shafts, stern glands, pulp grinder, piston heads and also in combination with firmer types as a lubricating component on accumulator and press rams.

SPECIFICATIONS	
pH range	6 to 8
Temperature limit	194°F (90°C)
Pump speeds	up to 1885 fpm (9.58 m/s)
Construction	Square braid
Material	Long flax fiber
Lubrication	Petroleum

in.	1/8	3/16	1/4	5/16	3/8	7/16	1/2	9/16	5/8	3/4	7/8	1
ft./lb.	89.5	50.0	32.5	18.0	13.8	10.4	7.8	6.8	5.6	3.6	2.7	2.0

Disclaimer: The temperature limits, pH ranges, pressure ratings, feet per box and shaft speeds shown throughout this pamphlet are representative; the service life and performance of these products can be affected by elevated temperatures and other operating conditions such as chemical resistance, shaft speeds, pressure and equipment in which that the product is being installed. The ratings supplied are suggested as a guideline and should only be used for evaluating your specific application. When in doubt, contact Robco or your ENVIROPAK distributor. *The information contained in the pamphlet should not be considered to be a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. In no event shall Robco be liable for any incidental or consequential damages resulting from the use, misuse or inability to use the products.* This exclusion applies regardless of whether such damages are sought based on breach of warranty, breach of contract, negligence, strict liability in tort, or any other legal theory.